


## MATERIAL SAFETY DATA SHEET (MSDS)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance  
 :  
 CAS No : 78-92-2  
 Product code : 0055B  
 Chemical structure :



Synonyms : sec-Butyl alcohol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Labogens Fine Chem Industries  
 1st Floor , Above Bank of India, Guru Vihar , Rahon Road,  
 Ludhiana Pb. (141007)  
 +91 9316777775, +91 7707855700  
[sales@labogens.com](mailto:sales@labogens.com) - [www.Labogens.com](http://www.Labogens.com)

#### 1.4. Emergency telephone number

Emergency number : +91 7707855700 (9:00am - 6:00 pm)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H226  
 Category 3  
 Serious eye damage/eye H319  
 irritation, Category 2  
 Specific target organ H335  
 toxicity — Single  
 exposure, Category 3,  
 Respiratory tract irritation  
 Specific target organ H336  
 toxicity — Single  
 exposure, Category 3,  
 Narcosis

Full text of classification categories and H statements : see section 16

# BUTAN-2-OL AR

## Safety Data Sheet

### Classification according to Directive 67/548/EEC or 1999/45/EC

Xi; R36

Xi; R37

R10

R67

Full text of R-phrases: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Warning

Hazard statements (CLP) : H226 - Flammable liquid and vapour  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing

## 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Name : BUTAN-2-OL AR

CAS No : 78-92-2

Full text of R- and H-phrases: see section 16

### 3.2. Mixture

Not applicable

# BUTAN-2-OL AR

## Safety Data Sheet

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth out with water. If you feel unwell, seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

#### 5.3. Advice for firefighters

No additional information available

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

# BUTAN-2-OL AR

## Safety Data Sheet

Hygiene measures : Wash ... thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.

Storage conditions : Keep container tightly closed. Store in original container. Store in a dry place.

Incompatible materials : Heat sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

Hand protection : protective gloves

Eye protection : Chemical goggles or safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Molecular mass : 74.12 g/mol

Colour : Clear Colorless.

Odour : sweet, fruity odor.

Odour threshold : 3.2 ppm

pH : 7

Relative evaporation rate (butylacetate=1) : No data available

Melting point : -115 °C

Freezing point : No data available

Boiling point : 99.5 °C

Flash point : 24 °C

Auto-ignition temperature : 4050 °C

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable  
Flammable liquid and vapour

# BUTAN-2-OL AR

## Safety Data Sheet

Vapour pressure	: 12 mm Hg at 20C
Relative vapour density at 20 °C	: 2.6
Relative density	: No data available
Density	: 0.808 g/cm <sup>3</sup>
Solubility	: Water: 12.5 g/100ml @ 20°C
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 3.5 cP @ 20 deg C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.017 - 0.098 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: 7
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

# BUTAN-2-OL AR

## Safety Data Sheet

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

<b>BUTAN-2-OL AR (78-92-2)</b>	
Viscosity, kinematic	4.33168317 mm <sup>2</sup> /s

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to ...
Additional information	: Handle empty containers with care because residual vapours are flammable.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 1120
UN-No. (IMDG)	: 1120
UN-No.(IATA)	: 1120

# BUTAN-2-OL AR

## Safety Data Sheet

UN-No.(ADN) : 1120  
UN-No. (RID) : 1120

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : BUTANOLS  
Proper Shipping Name (IMDG) : BUTANOLS  
Proper Shipping Name (IATA) : BUTANOLS  
Proper Shipping Name (ADN) : BUTANOLS  
Proper Shipping Name (RID) : BUTANOLS  
Transport document description (ADR) : UN 1120 BUTANOLS, 3, III, (D/E)  
Transport document description (IMDG) : UN 1120 BUTANOLS, 3, III  
Transport document description (IATA) : UN 1120 BUTANOLS, 3, III  
Transport document description (ADN) : UN 1120 BUTANOLS, 3, III  
Transport document description (RID) : UN 1120 BUTANOLS, 3, III

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



#### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



#### RID

# BUTAN-2-OL AR

## Safety Data Sheet

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3



### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III  
Packing group (ADN) : III  
Packing group (RID) : III


### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : F1  
Limited quantities (ADR) : 5L  
Excepted quantities (ADR) : E1  
Packing instructions (ADR) : P001, IBC03, LP01, R001  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T2  
Portable tank and bulk container special provisions (ADR) : TP1  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Operation (ADR) : S2  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •2YE

#### - Transport by sea

Special provision (IMDG) : 223  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1



# BUTAN-2-OL AR

## Safety Data Sheet

EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
MFAG-No	: 129

### - Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provision (IATA)	: A3
ERG code (IATA)	: 3L

### - Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### - Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

BUTAN-2-OL AR is not on the REACH Candidate List

BUTAN-2-OL AR is not on the REACH Annex XIV List

# BUTAN-2-OL AR

## Safety Data Sheet

### 15.1.2. National regulations

#### Germany

AwSV/VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to VwVwS, Annex 2; WGK No 40)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

#### Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H319;H335;H336>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
R10	Flammable
R36	Irritating to eyes
R37	Irritating to respiratory system
R67	Vapours may cause drowsiness and dizziness
Xi	Irritant

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*